

CROSSOVER[®]

In a class by itself.

The world's first small chassis stacked washer & dryer combo engineered to commercial laundry standards for your business needs.



PROFESSIONAL SPECIFICATIONS

Serving the Route and OPL laundry markets, Crossover Series stacked washer/dryer meet business demands with durability, energy savings and customer satisfaction.

FEATURES AND BENEFITS

- ✓ 15,000+ cycle machine life design
- ✓ Large high security coin vault
- ✓ 4 professional wash programs, + 2 cycle options
- ✓ Field adjustable water levels + cycle
- ✓ Top quality SKF bearings in heavy duty assembly
- ✓ 3 seals (with 5 lips) protect bearings
- ✓ AC motor (no brushes)
- ✓ Professional 8-point suspension & Pump Drain Standard
- ✓ Solid steel counterweights—no concrete
- ✓ Commercial grade construction
- ✓ 22+ lb capacity and 7.5 cu ft drum
- ✓ Stainless steel fixed lint screen and roller supported tumbler
- ✓ Tapered sealed ribs bring load forward improving dryer performance

BEST CUSTOMER EXPERIENCE

- ✓ Superior oversuds and unbalance tolerance
- ✓ Extra large door opening for easy loading and unloading
- ✓ Heavy-duty door hinge
- ✓ High speed 300G maximum extraction
- ✓ Simple, easy to use operation
- ✓ Axial airflow ensures the shortest drying time
- ✓ Easy clean lint screen
- ✓ Large capacity tumbler can handle oversized loads

MARKET READY DESIGN

- ✓ Space-saving 27" wide to minimize floor space
- ✓ Quiet operation
- ✓ Liquid chemicals are fully diluted with water

NON-METERED STACKING WASHER AND DRYER—(GAS HEAT DRYER)
Model No. WDSGNM

NON-METERED STACKING WASHER AND DRYER—ELECTRIC Model No. WDSENM

Laundrylux[®]

866.580.1010 ✓ laundrylux.com



CEE TIER III
COMPLIANT

CROSSOVER STACKED WASHER/DRYER

CROSSOVER STACK WASHER/DRYER SPECIFICATIONS

Model No.	Non-Metered/Card Ready - Gas WDSGNM
Model No.	Non-Metered/Card Ready - Electric WDSNEM
Motor	1/3 HP
Electrical Rating (Gas Model)	120VAC/60Hz/2W/1-phase
Electrical Rating (Electric Model)	208-240V/ 60Hz/1-phase
Breaker/Fuse Requirements (Gas)	15A
Breaker/Fuse Requirements (Electric)	30A
Cylinder Volume	7.5 cu ft/ 212.4 liters
Cylinder Diameter	25 3/4 in
Cylinder Depth	24 in
Capacity (Dry Weight)	10Kg/22lbs
Door Opening	17 1/4 in (438 mm)
Airflow (Gas & Electric)	220 cfm
Electric Heating (240VAC)	5.4 kW
Gas Heating	26,000 Btu/hr (6,550 kcal/hr)
Gas Connection	3/8 in MNPT
Tumbling Speed	50 rpm
Exhaust Connection	4in Dia.
Overall Dimensions	W D H: 27 1/8 x 31 3/4 x 77 1/2 in
Overall Dimensions	W D H: 686 x 807 x 1968 mm
Approximate Net Weight	151 lbs

*NOTE: the correct measurement of extraction efficiency is G-force, not RPM. A higher RPM does not mean greater extraction, which depends on cylinder diameter.



Refer installation and servicing to qualified, licensed personnel. Always read installation and Operating Manuals and consult local codes before installation. Protect machines with properly rated circuit breakers ONLY. Warranty void if not properly installed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

Laundrylux offers a complete line of Electrolux Professional and Wascomat Commercial Laundry equipment.

Laundrylux®

866.580.1010 ✓ laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096

Sales and Administration Tel: 516-371-4400 • Fax: 516-371-4204 • sales@laundrylux.com

Spare Parts Tel: 516-371-2000 • Fax: 516-371-4029 • parts@laundrylux.com

Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010