

Electrolux 100 G-force Washers

N-Series Solid-Mount, Normal Spin for OPL

Electrolux washers feature Compass Pro, low water consumption, and robust design.

Electrolux Professional 100 G-Force extraction normal spin washers combine world-class reliability with innovative features and programmability.

Electrolux washers increase your productivity, lower utility costs, and provide significant electrical and gas savings. With innovative design and high performance features, Electrolux washers come standard with Compass Pro for easy customization and flexibility.

FEATURES AND BENEFITS:

- Low water consumption
- Single phase 220 volt electrical service reduces installation costs
- Convenient 4-compartment supply dispenser lets you conveniently add all laundry supplies before starting the wash
- Provisions to connect up to 5 liquid supplies
- Door unlocks immediately at the end of final cycle. No delays.
- Heavy-duty construction with robust steel door and lock
- Stainless and galvanized steel in all vital parts for maximum rust protection
- Inverter driven motor for smooth and quiet operation, high efficiency
- External liquid manifold improves reliability, workflow, and operation. Best design in the industry. Chemicals are diluted in water reservoir. Reduces maintenance
- SuperBalance guarantees the correct extraction force, longer machine life
- **Option:** Voice Guidance

COMPASS PRO MICROPROCESSOR OFFERS

Compass Pro microprocessor provides the ultimate in flexibility and control over your laundry operations.

- Up to 50 programs, 15 custom
- Large display and one control knob for easy program selection
- Two languages displayed simultaneously
- Smart Start - real-time clock for delayed start
- Detailed user statistics and programmability
- Reduce operator error by displaying only the programs you use



Available in 20, 25, 30, 45, 62 & 77 lb. capacities. Vertical blue wave front panel standard. Stainless available. Most sizes available in 220 or 120 volt, single phase.

Electrolux models are designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.



Designed by experts. Inspired by you.

Electrolux "N" Series, 100G Washers	W585N		W5105N		W5130N		W5180N		W5250N		W5330N	
Capacity (lb/kg)	20	9	25	11	30	14	45	20	62	28	77	35
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	28 7/16	722	27 7/16	697	31	787	36	914	40 1/2	1029	43 7/8	1114
Height (in/mm)	44 5/8	1133	47 15/16	1217	47 7/8	1216	52 15/16	1345	56 1/8	1426	57 11/16	1465
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 1/4	310	14 3/8	365	14 3/8	365	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft ³ /l)	3	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103
Extract (rpm/G-Force)	587 / 100		548 / 100		548 / 100		525 / 100		497 / 100		474 / 100	
Dynamic floor load (lb/kN)	382 +/- 697	1.7 +/- 3.1	427 +/- 562	1.9 +/- 2.5	540 +/- 697	2.4 +/- 3.1	652 +/- 877	2.9 +/- 3.9	854 +/- 1102	3.8 +/- 4.9	1034 +/- 1259	4.6 +/- 5.6
Dynamic frequency (Hz)	9.3		9.1		9.1		8.8		8.3		7.9	
Noise level (dBA) in extraction	<70		<70		<70		<72		<71		<74	
Crated width - (in/mm)	27 3/16	690	29 1/2	750	29 1/2	750	30 11/16	780	33 7/8	860	37	940
Crated depth - (in/mm)	32 11/16	830	35 1/16	890	37 3/8	950	39 3/16	995	43 11/16	1110	47 1/16	1195
Crated height - (in/mm)	48	1219	53 1/8	1350	53 1/8	1350	56 7/16	1434	61 1/4	1556	62 7/16	1586
Crated weight (lb/kg)	276	126	364	166	370	169	522	238	615	280	717	326
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.5 / 2.4 / 15		0.7 / 3.4 / 15		0.8 / 3.9 / 15		0.9 / 4.3 / 15		1.1 / 5.3 / 15		1.2 / 5.8 / 15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		120/60/1	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.6 / 5.0 / 15		0.8 / 5.8 / 15		0.9 / 7.5 / 15		1.0 / 8.3 / 15		1.2 / 10.0 / 15		1.3 / 10.8 / 15	
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600
Approx Water usage (gal / liters @ full load)	12.9	49	16.3	61.7	20.9	79	30.4	115	42.8	162	53.6	203
Modified Energy Factor	n/a											
Water Factor (Gal per cycle/drum volume)	4.3		4.4		4.5		4.8		4.8		4.6	
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.												



Electrolux Professional Line 5000 The all-in-one business solution for your on-premises laundry.



Greatest flexibility with Compass Pro®

- Up to 50 programs, 15 custom
- Automatic Savings (AS)
- One control knob for easy program selection
- Displays 2 languages at the same time
- Smart Start - real-time clock for delayed start
- Detailed user statistics and programmability
- Reduce operator error by displaying only the programs you use.



Extended lifetime due to Super Balance™

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



External Liquid Chemical Manifold – Best design in the industry

- Chemicals are diluted in water reservoir
- Improves reliability, operation, workflow
- Reduces maintenance

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

T 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Technical Care: 516-371-0700 • F 516-371-4029 • techcare@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010