

Electrolux 450 G-force Washers

H-Series Soft-Mount, High Spin for Coin/Card

**At 450G, your customers can wash and dry in less than an hour.
You'll save energy and up to 50% on water – automatically.**

Electrolux Professional 450 G-Force high-speed extraction washers minimize drying time and provide significant electrical and gas savings. Self-service laundries benefit from faster throughput (freeing up dryers, folding tables and parking spots) which creates higher profits. Your customers can even receive a text message (option) notifying them when their wash is done and ready for unloading! Increase your profits and create customers for life with the unique features of Electrolux Professional washers. Add a row of H-Series washers to your store to boost your profits and lower your operating costs.

FEATURES AND BENEFITS:

- AS (Automatic Savings) - saves up to 50% on water. With every wash cycle, AS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs
- Extremely low water and energy consumption
- Super fast drying
- Convenient four compartment detergent box
- Soft-mount for easy installation on wood floors, upper levels, & over basements
- Heavy-duty construction with robust steel door and lock
- Stainless and galvanized steel in all vital parts for maximum rust protection
- Power Balance ensures the correct extraction and maximum savings in drying time. Minimizes stress on machines for trouble free operation and longer machine life
- Sanitizing Rinse for greater customer satisfaction and additional revenue
- Text messaging - option
- Voice guidance - option

COMPASS PRO MICROPROCESSOR OFFERS:

- Easy to customize programs
- Large display and one control knob for easy program selection
- More than 20 languages available – displays two languages, simultaneously
- Real time clock for time of day pricing, happy hour pricing and promotions
- Heavy Soil and Extra Rinse option buttons for higher customer satisfaction and increased revenue
- Detailed user statistics and programmability



Available in 18, 25, 30, 45, 60 & 75 lb. capacities.
Vertical blue wave front panel standard in 18 and 25 lb. models.

Electrolux H-Series models are Energy Star rated up to 45 lb. capacity. They meet strict energy efficiency guidelines set by the EPA and US Department of Energy.



Our larger machines are also designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.



Designed by experts. Inspired by you.



Electrolux "H" Models, Soft-Mount 450G High-Spin – Coin/Card Washers	Energy Star rated up to 45 lb. capacity											
	W575H		W5105H		W5130H		W5180H		W5240H		W5300H	
Capacity (lb/kg)	18	8	25	11	30	14	45	20	60	27	75	33
Width (in/mm)	28 3/8	720	32 11/16	830	35 13/16	910	38 3/16	970	40 3/16	1020	40 3/16	1020
Depth (overall) (in/mm)	28 3/8	721	29 13/16	757	32 5/16	821	37 1/4	947	39	990	44 3/4	1134
Height (in/mm)	44 9/16	1132	47 11/16	1212	52 3/4	1340	56	1426	57 4/8	1462	57 1/2	1462
Height to bottom of door (in/mm)	14	355	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500	19 11/16	500
Door opening diameter (in/mm)	12 3/16	310	14 3/8	365	15 9/16	395	17 1/8	435	17 1/8	435	17 1/8	435
Cylinder volume (ft3/l)	3.6	75	3.7	105	4.6	130	6.4	180	8.5	240	10.6	300
Drain outlet diameter (in/mm)	2 15/16	75	2 15/16	75	2 15/16	75	2 15/16	75	2 15/16	75	2 15/16	75
Height to centerline of drain (in/mm)	4 1/16	103	4 1/16	103	4 1/16	103	3 15/16	100	3 15/16	100	3 15/16	100
Extract (rpm/G-Force)	1245 / 450		1165 / 450		1115 / 450		1055 / 450		1005 / 450		950 / 400	
Dynamic floor load (lb/kN)	427 +/- 112 1.9 +/- 0.5		562 +/- 112 2.5 +/- 0.5		697 +/- 112 3.1 +/- 0.5		944 +/- 225 4.2 +/- 1.0		1169 +/- 225 5.2 +/- 1.0		1394 +/- 292 6.2 +/- 1.3	
Dynamic frequency (Hz)	20.8		19.4		18.6		17.6		16.8		15.8	
Noise level (dBA) in extraction	<75		<78		<79		<85		<85		<84	
Crated width - (in/mm)	29 15/16	760	33 7/8	860	37 13/16	960	40 3/16	1020	41 5/16	1050	41 5/16	1050
Crated depth - (in/mm)	32 1/2	825	34 1/4	870	37 13/16	960	41 5/16	1050	42 15/16	1090	47 1/4	1200
Crated height - (in/mm)	50	1270	53 1/8	1350	58 11/16	1490	61 13/16	1570	63	1600	63	1600
Crated weight (lb/kg)	373	170	474	216	611	278	816	371	974	443	1274	580
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.7 / 3.4 / 15		1.1 / 5.3 / 15		1.5 / 7.2 / 15		2.5 / 12.0 / 15		2.7 / 13.0 / 20		3.0 / 14.4 / 20	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1							
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.8 / 6.7 / 15		1.2 / 10 / 15		1.7 / 14.2 / 20				n/a			
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	39-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600
Approx Water usage (gal / liters @ full load)	9.6	36	10.7	41	16.8	64	20.3	77	30.2	115	38.4	145
Modified Energy Factor	2.7		2.7		2.6		2.4		2.4		2.4	
Water Factor (Gal per cycle/drum volume)	3.9		3.4		4.0		3.9		3.9		3.9	
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.												



Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



Greatest flexibility with Compass Pro™

- Real-time clock for time-of-day and happy hour pricing
- Multi-language menu selection
- Easy to customize
- Simple to use
- Revenue generating option buttons



Extended lifetime due to Power Balance™

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



Cost savings in water & energy with Automatic Savings (AS)

- Determines load weight and adds precisely the correct amount of water
- Up to 50% water savings - automatically
- Reduces water and energy consumption

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

T 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Technical Care: 516-371-0700 • F 516-371-4029 • techcare@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010