

Wascomat Dual-Use Wetclean Systems

Wetcleaning is incredibly effective for professionally cleaning all kinds of fabrics and textiles. With Wascomat eco-friendly solutions, you will be less dependent on the need for harsh chemicals, while delivering the highest quality results to your customers. **A smart addition to traditional drycleaning methods.**



Wetcleaning Washers

- Feature a special 2 gallon sump which allows for complete mixture with shrinkage resistant additives prior to exposure to the garments.
- Steam heated with precise temperature control for long soaks for the most stubborn stain removal.
- Program to the exact water levels and exact wash and extraction speeds.
- Run laundry programs as well to do shirts, comforters, sleeping bags and bachelor bundles. Even an overnight soak!

Wetcleaning Dryers

- Feature standard steam heat, reversing cylinder and RMC.

Residual Moisture Control

Wascomat's Wetclean TD Dryers include our exclusive, accurate and fully-automatic Residual Moisture Control (RMC) system.

RMC prevents damage to garments caused by overdrying and reduces lint and wrinkles by automatically stopping the dryer when the exact pre-set moisture level is reached. The amount of residual moisture in the fabric is important for proper finishing.

Environmentally safe.

Wascomat dual-use Wetclean Systems are an environmentally safe, non-polluting alternative to perc. With the push of a button, the Wascomat wetcleaner converts to an ideal washer for laundering shirts, comforters, drapes and "wash-dry-fold" laundry.

Customers prefer wetcleaning.

Your customers will immediately see, feel and smell the difference in their clothing: **colors are brighter, fabrics softer, and the smell is fresh and clean – no chemical smell or residue.**



Clarus® Control

Wascomat's "Dual-use" Wetclean washers are equipped with Clarus® Control for easy programming and superior cleaning results. Programmable Memory Card can be used to start or install programs created on your computer or on the control panel.


Clarus® manages wetcleaning and laundry washing processes by precisely controlling all important functions including water temperatures & levels, extract speed, and cleaning and wash cycle times.


Custom Programs are Simple


Automatic and easy to program – Clarus® microprocessor control lets you create up to 192 custom laundry and wetcleaning wash programs and controls 8 individual trigger signals for liquid and powder supply injection.


All programs can easily be entered on the Clarus® Control panel on the front of the machine.

Wascomat Dual-Use Wetclean Models

	TD Series Wetclean Dryers Models with RMC	TD35		TD67		TD83		TD100		TD135	
	Capacity (lb/kg)	35	16.1	67	30.5	83	37.5	100	45	135	60
	Width (in/mm)	27 15/16	710	37 13/16	960	37 13/16	960	50 13/16	1290	50 13/16	1290
	Depth (in/mm)	45 1/2	1155	51 3/4	1315	59 7/16	1510	51	1295	58 7/16	1485
	Height overall (in/mm)	65 15/16	1675	73 7/16	1855	73 7/16	1855	97 1/16	2465	97 1/16	2465
Height without heating unit				n/a				77 3/8	1965	77 3/8	1965

	200 G-Force Extract, Solid-Mount SUPER Wetclean Washer Models	SU645ca		Call for more details on electrical requirements and more.	Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, inverse-time, common-trip, industrial-type circuit breakers ONLY. Warranty void if not properly installed. Advise when placing order if dryers are for installation at altitudes in excess of 1000 feet above sea level, as this may require a gas-orifice change. Contact Laundrylux for more information and availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.
	Capacity (lb/kg)	45	20		
	Width (in/mm)	29 1/2	750		
	Depth (overall) (in/mm)	36	915		
	Height (in/mm)	52 3/16	1325		

	300 G-Force Extract, Solid-Mount Wetclean EXSM Washer Models	EXSM665ca		Call for more details on electrical requirements and more.	Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, inverse-time, common-trip, industrial-type circuit breakers ONLY. Warranty void if not properly installed. Advise when placing order if dryers are for installation at altitudes in excess of 1000 feet above sea level, as this may require a gas-orifice change. Contact Laundrylux for more information and availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.
	Capacity (lb/kg)	65	29		
	Width (in/mm)	36 13/16	935		
	Depth (overall) (in/mm)	38 3/16	970		
	Height (in/mm)	57 5/16	1455		
	Extraction (rpm/g factor) (max)	805/300			
Frequency Controlled Motor	Standard				

	300 & 350 G-Force Extract, Soft-Mount Wetclean EX Washer Models	EX645ca		EX660ca		EX675ca		Call for more details on electrical requirements and more.	Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, inverse-time, common-trip, industrial-type circuit breakers ONLY. Warranty void if not properly installed. Advise when placing order if dryers are for installation at altitudes in excess of 1000 feet above sea level, as this may require a gas-orifice change. Contact Laundrylux for more information and availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.
	Capacity (lb/kg)	45	20	60	27	75	33		
	Width (in/mm)	38 3/16	970	40 3/16	1020	40 3/16	1020		
	Depth (overall) (in/mm)	37 3/16	945	37 5/8	955	44 11/16	1135		
	Height (in/mm)	55 1/2	1410	56 7/8	1445	56 7/8	1445		
	Extraction (rpm/g factor) (max)	930/350		890/350		820/300			
	Frequency Controlled Motor	Standard		Standard		Standard			

Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing.



Wascomat

Laundrylux

800.645.2204 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

