

EXSM Series 220-300G Solid Mount Washers

Built to last, Wascomat EXSM solid mount washers are designed for efficiency and superior wash results. Precision-engineering reduces downtime and improves machine reliability. The high G-force extraction cuts drying time resulting in lower utility costs and higher laundry room productivity.



Features and Benefits

- AS (Automatic Savings) - Save up to 50% on water with AS, automatically. With every wash cycle, AS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs (*Note: The 135 lb washer does NOT have AS*)
- Heavy-duty construction for demanding applications
- Efficient frequency-controlled motor reduces peak power demand by 50% for big energy savings
- Optional steam injection for precise control of water temperature
- Built-in connection for automatic liquid injector
 - Compass Pro provides 5 liquid chemical signals
 - Clarus provides 4 liquid chemical signals (expandable to 8)
- Standard 4-compartment supply dispenser for liquid or powder supplies on 65 lb and 80 lb models
- Optional 5-compartment supply dispenser for liquids or powders available on 135 lb washer
- Built-in diagnostics and statistics

Compass Pro

- Customize wash programs to raise efficiencies and lower costs
- More than 20 languages available — display two simultaneously
- Reduce operator error by displaying only the programs you use
- Up to 50 programs available; ability to create 15 custom programs
- Real-time clock for delayed start

Clarus Control

- Fully programmable microprocessor
- All wash parameters can be programmed and customized
- Programming from keypad or download via memory card

220-300 G-Force Extraction

The perfect balance of speed, performance, and BIG savings. High-speed spin removes more water for faster drying times and better wash performance.

Two Control Options

Choose between the advanced Compass Pro or Clarus Control.

Best in the Industry

The Wascomat external liquid chemical manifold offers improved reliability, maintenance, and flushing using a built-in water reservoir to promote 24/7 diluted chemicals in the dispensing system.

Wascomat EXSM Series, 220-300G Washers	EXSM765		EXSM780		EXSM 7135	
Capacity (lb/kg)	65	30	80	36	135	60
Width (in/mm)	36 3/4	933	43 7/8	1115	46 3/16	1173
Depth (overall) (in/mm)	38 3/4	985	44 1/8	1121	50 5/8	1286
Height (in/mm)	57 5/16	1456	61 13/16	1570	65 7/8	1673
Height to bottom of door (in/mm)	20 1/2	520	21	534	21 1/4	540
Door opening diameter (in/mm)	16 1/8	410	21 1/16	535	21 1/16	535
Cylinder volume (ft ³ /l)	9.9	280	12.4	350	21.2	600
Drain outlet diameter (in/mm)	2 15/16	75	2 15/16	75	2 15/16	75
Height to centerline of drain (in/mm)	4 11/16	119	4 13/16	122	4 1/16	103
Extract (rpm/G-Force)	805 / 300		650 / 220		630 / 220	
Dynamic floor load (lb/kN)	1101 +/- 2135	4.9 +/- 9.5	1551 +/- 2405	6.9 +/- 10.7	2248 +/- 3507	10 +/- 15.6
Dynamic frequency (Hz)	13.4		10.8		10.5	
Noise level (dBA) in extraction	<75		<82		<84	
Crated width - (in/mm)	43 5/16	1100	44 7/8	1140	47 5/8	1210
Crated depth - (in/mm)	45 11/16	1160	54 5/16	1380	55 1/8	1400
Crated height - (in/mm)	62 5/8	1590	67 11/16	1720	72 13/16	1850
Crated weight (lb/kg)	882	401	1272	579	1920	873
Electrical Requirements (standard)						
Voltage/frequency/phase	208-240/60/1 or 3-		208-240/60/1 or 3-		208-240/60/3-	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 7.2 / 15		1.8 / 8.6 / 15		2.6 / 7.2 / 15	
Voltage/frequency/phase	480 / 60 / 1 or 3-		480/60/1 or 3-		480/60/3-	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 3.1 / 10		1.8 / 3.8 / 10		2.6 / 3.1 / 10	
Water Information						
Inlet fittings (* = 3 inlets)	3/4"	DN20	3/4"	DN20	1"	DN25
Flow (gpm/lpm @ 45 psi) (each inlet)	16	60	16	60	25	110
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600
Approx Water usage (gal / liters @ full load)	n/a					
Modified Energy Factor						
Water Factor (Gal per cycle/drum volume)						
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.						



* **NOTE:** The 135 lb washer does NOT have AS



Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing.



Laundrylux

800.645.2204 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010