

TD Series Stack and Single Pocket Dryers

Wascomat TD Dryers are precision-engineered for efficiency, ease of use, and superior drying results. Our single pocket dryers feature easy-to-use Compass Pro control. Wascomat dryers are the best choice for reliability, durability, and customer satisfaction. Perfect for coin/card laundries, customers will appreciate the fast drying and user-friendly controls.



Features and Benefits

- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the best-in-the-world drying performance with the fastest drying time and the lowest energy consumption
- Extra large doors make loading and unloading easy
- Easy to clean lint screen — best in the industry
- Quiet operation — Wascomat dryers are designed to keep noise level below 70 dB (A)
- Reverse drum operation (option) minimizes tangling and wrinkling, and improves dryer efficiency
- Sturdy drum suspension with double-sealed bearings and belt drive for "workhorse" durability
- Provide unsurpassed control of temperatures, to avoid damage to linens, and maximize reliability
- Easy installation


Single Pocket Dryer Features

- **Axial Airflow** and tight construction for extremely low energy consumption
 - Dries faster, saving up to 25% in gas
- **Compass Pro Program Control**
 - Large display with control knob for easy program selection
 - Language selection — displays two languages at one time
 - Customize programs to increase customer satisfaction
- **Selecta II**
 - 4 temperature settings
 - Displays remaining drying time
 - Coin, token, debit card compatible
 - Complete diagnostics & service model
 - Top Exhaust Kit (optional)


A Long History of Excellence

Wascomat dryers offer reliability, durability and significant energy savings for self-service laundries.

TD Dryer Controls



Compass Pro — Available on single pocket dryers



Selecta II Coin/Card — Available on 30x30 and 45x45L stack dryers

Wascomat TD Dryers - Stack & Single Pocket	TD 30x30		TD 45x45L		TD35		TD67		TD83	
Capacity (lb/kg)	2 x 35	2 x 16	2 x 50	2 x 22.7	35	16	67	31	83	37.5
Width (in/mm)	31 1/8	790	34 3/16	868	28 1/16	713	37 13/16	961	37 13/16	961
Depth (in/mm) (Steam heat add 6" (150mm) to T5x models)	43 7/8	1115	52 3/5	1336	47 5/8	1210	53 3/4	1365	61 7/16	1560
Depth with door open (in/mm) (Steam heat add 6" (150mm) to T5x models)	72 7/16	1840	85 15/16	2183	74 1/8	1883	92 1/8	2340	93 5/16	2370
Height Overall (in/mm)	76 3/8	1940	82 1/8	2086	66 1/2	1688	73 9/16	1869	73 1/8	1857
Height without heating unit (in/mm)	n/a									
Door opening diameter (in/mm)	22 13/16	580	27 1/16	687	22 5/6	580	31 7/8	810	31 7/8	810
Cylinder volume (ft ³ /l)	2 x 10.6	2 x 300	2 X 15	2 X 423	10 3/16	290	19.4	550	23.8	675
Crated Weight (lb/kg)	683	311	880	440	453	206	664	302	695	316
Utility Connections										
Exhaust duct diameter (in/mm)	8	200	8	200	8	200	8	250	8	250
Exhaust static pressure (inches H2O / mbar) (max at 60Hz)	0.75	1.9	0.75	1.9	0.75	1.9	0.75	1.9	0.75	1.9
Gas connection (One inlet supplies both pockets on stack dryers)	1/2 MNPT		3/4 MNPT		1/2 MNPT		1/2 MNPT		1/2 MNPT	
Steam connection, inlet & condensate	n/a				1 MNPT		1 MNPT		1 MNPT	
Energy Data										
Gas (Btu/hr)	2 x 71,650		2 x 94,000		71,700		112,700		143,400	
Airflow (ft ³ /min / m ³ /hr) (gas heat)	2 x 353	2 x 600	2 x 500	2 x 850	360	610	553	940	671	1140
Electric Heating Power (kW) @ 208-240V/3Ø	9 or 13.5 or 18			n/a	13.5 or 18		18 or 24 or 32		32 or 40	
Airflow (ft ³ /min / m ³ /hr) (elec. heat)	2 x 353	2 x 600	324		550	553	940	671	1140	
Steam Consumption (lb/hr / kg/hr) (approximate)	n/a		80		36	118	54	150 / 68		
Airflow (ft ³ /min / m ³ /hr) (steam heat)	n/a		406		690	636	1080	812	1380	
Electrical Requirements										
Current, gas or steam, 120 V/60Hz(full load/circuit breaker)	2 x 9A / 2 x 15A		2 x 14A / 2 x 20A		7.5A (15A)		15.8A (20A)		16A (20A)	
Current, gas or steam, 208-240 V/60Hz/1Ø(full load/circuit breaker)	2 x 4.5A / 2 x 15A		2 X 7A / 2 X 15A		3.8A (15A)		8.2A (15A)		8.2A (15A)	
Current, gas or steam, 208-240 V/60Hz/3Ø(full load/circuit breaker)	n/a				3.7A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	Depends upon Voltage and power selected. Contact Laundrylux Sales Department.									
Alternate Voltages										
Alternate voltages available. Contact Laundrylux Sales Department.										
Supply Pressures										
Natural Gas (inches H2O / mbar)					3.5-12 / 9-30					
Propane (inches H2O / mbar)					10-13 / 25-30					
Steam (psi / bar) (max)	n/a						145 / 10			
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.										

Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing.



Laundrylux
800.645.2204 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com
Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com
Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010



TD45x45 is CSA certified. Other TD dryers are ETL certified.