

# Electrolux 220-300 G-force Washers

## X-Series Solid-Mount, Extra Spin for OPL

### Electrolux smart washers will forever change the way you do laundry

Imagine a washer smart enough to weigh the load size and add precisely the correct amount of water. Imagine a laundry chemical controller smart enough to adjust dosing for accurate water ratio each time.

Electrolux Professional washers do all that and more! An estimated 60-70% of washers are underloaded, wasting water, chemicals, and energy. That's why Electrolux developed Automatic Savings (AS), a unique feature that automatically matches water consumption to load size. Combine that with Smart Dosing which adjusts laundry chemicals to water ratio, and you will see immediate savings and superior wash results – every time, automatically.

#### FEATURES AND BENEFITS:

Electrolux Professional 220-300 G-Force high-speed extraction washers minimize drying time and provide significant electrical and gas savings. On-premises laundries benefit from higher productivity and lower costs. On-premises laundries can go right to flatwork finishing equipment after conditioning items in the dryer. You'll get superior results while saving valuable time and money.

- Save up to 50% on water with AS, automatically (available on 65 & 80 lb models)
- Smart Dosing automatically adjusts the ratio of laundry chemicals to water resulting in lower costs and a superior wash
- Convenient 4-compartment supply dispenser
- Provisions to connect up to 5 liquid supplies
- Heavy-duty construction with robust steel door and lock, hinges wide apart
- Stainless and galvanized steel in all vital parts for maximum rust protection
- Super Balance (on 65 lbs) / Power Balance (on 85 lbs and up) guarantees the correct extraction force, longer machine life
- External liquid manifold improves reliability, workflow
- **Option:** Voice Guidance

#### COMPASS PRO MICROPROCESSOR OFFERS:

- Up to 50 programs, 15 custom
- Large display and one control knob for easy program selection
- Two languages displayed simultaneously
- Smart Start - real-time clock for delayed start
- Detailed user statistics and programmability
- Reduce operator error by displaying only the programs you use



*Available in 65, 80, and 135 lb. capacities. 5-year limited replacement parts warranty - best in the industry! \*The 135 lb model does NOT have AS.\**



**Designed by experts.** Inspired by you.

# Electrolux Professional Line 5000 The all-in-one business solution for your on-premises laundry

Electrolux "X" Models, 300G Washers	W5280X		W5350X		W5600X	
Capacity (lb/kg)	65	30	80	36	135	60
Width (in/mm)	36 3/4	933	43 7/8	1115	46 3/16	1173
Depth (overall) (in/mm)	38 3/4	985	44 1/8	1121	50 5/8	1286
Height (in/mm)	57 5/16	1456	61 13/16	1570	65 7/8	1673
Height to bottom of door (in/mm)	20 1/2	520	21	534	21 1/4	540
Door opening diameter (in/mm)	16 1/8	410	21 1/16	535	21 1/16	535
Cylinder volume (ft <sup>3</sup> /l)	9.9	280	12.4	350	21.2	600
Drain outlet diameter (in/mm)	2 15/16	75	2 15/16	75	2 15/16	75
Height to centerline of drain (in/mm)	4 11/16	119	4 13/16	122	4 1/16	103
Extract (rpm/G-Force)	805 / 300		650 / 220		630 / 220	
Dynamic floor load (lb/kN)	1101 +/- 2135	4.9 +/- 9.5	1551 +/- 2405	6.9 +/- 10.7	2248 +/- 3507	10 +/- 15.6
Dynamic frequency (Hz)	13.4		10.8		10.5	
Noise level (dBa) in extraction	<75		<82		<84	
Crated width - (in/mm)	43 5/16	1100	44 7/8	1140	47 5/8	1210
Crated depth - (in/mm)	45 11/16	1160	54 5/16	1380	55 1/8	1400
Crated height - (in/mm)	62 5/8	1590	67 11/16	1720	72 13/16	1850
Crated weight (lb/kg)	882	401	1272	579	1920	873
<b>Electrical Requirements (standard)</b>						
Voltage/frequency/phase	208-240/60/1 or 3 ~		208-240/60/1 or 3 ~		208-240/60/3~	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 7.2 / 15		1.8 / 8.6 / 15		2.6 / 7.2 / 15	
Voltage/frequency/phase	480 / 60 / 1 or 3~		480/60/1 or 3~		480/60/3~	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 3.1 / 10		1.8 / 3.8 / 10		2.6 / 3.1 / 10	
<b>Water Information</b>						
Inlet fittings (* = 3 inlets)	3/4"	DN20	3/4"	DN20	1"	DN25
Flow (gpm/lpm @ 45 psi) (each inlet)	16	60	16	60	25	110
Recommended water pressure (psi/kPa)	30 - 90	200-600	30 - 90	200-600	30 - 90	200-600
Approx Water usage (gal / liters @ full load)	n/a					
Modified Energy Factor						
Water Factor (Gal per cycle/drum volume)						
<p><i>Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.</i></p>						



## Greatest flexibility with Compass Pro®

- Up to 50 programs, 15 custom
- Automatic Savings (AS)
- One control knob for easy program selection
- Displays 2 languages at the same time
- Smart Start - real-time clock for delayed start
- Detailed user statistics and programmability
- Reduce operator error by displaying only the programs you use.



## Cost savings in water & energy with Automatic Savings (AS)

- Determines load weight and adds precisely the correct amount of water and detergent
- Up to 50% water savings - automatically
- Reduces chemical usage
- Available on 65 & 80 lb models



## Extended lifetime due to Power Balance / Super Balance™

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



## Efficiency and Economy Savings with Smart Dosing

- Automatically calculates the correct amount of detergent
- Tangible results in efficiency, costs, and cleaning results
- Cuts chemical costs
- Customers notice results

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

# Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338  
T 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Technical Care: 516-371-0700 • F 516-371-4029 • techcare@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010