



# 130G HARD-MOUNT WASHER LIGHT DRY EXTRACTION

OUR BEST VALUE WASHER.  
BETTER THAN EVER.

With a dual language display and the ability to store up to 48 wash programs, Compass Pro gives your operators an effortless laundry experience. Loaded with energy and water-saving technology, this 130G washer will help you optimize your laundry operation.



## INNOVATIVE TECHNOLOGY

Increased extraction power delivers speed in more than a name.

### 130 G-FORCE SPIN

We've upgraded our entry-level washer to 130G force spin. More water extracted during the spin cycle leads to shorter dry times and longer linen life.

### SUPER BALANCE

Maintain high-spin performance and extend the life of your washer with our Super Balance technology.

Don't wash efficiency down the drain. Reduce costs — automatically.

### ULTRA FLAT DRAIN VALVE

Other washers waste up to 1 1/2 gallons of water every wash. Our ultra flat drain valve helps us save 97% in dead water vs our competitors.

### EFFICIENT DOSING

Reduce chemical costs by over 30%. Our dosing technology weighs each load and adds the optimum volume of soap and other chemicals to achieve the best wash results.

Optimize your on-premises laundry operation.

### COMPASS PRO

With a dual-language display and 48 programmable wash options, Compass Pro allows laundry operations to optimize their laundry room and eliminate user error.

### ERGONOMIC DESIGN

Electrolux Professional washers are certified to international standards of ergonomics, making your laundry room a healthier and more productive workplace.

	ELD-620	ELD-625	ELD-630	ELD-645	ELD-665	ELD-685
DRY WEIGHT CAPACITY (LB/KG)	20   9	25   11	30   14	45   20	65   29	85   39
WIDTH (IN/MM)	26   660	28 3/8   720	28 3/8   720	29 1/2   750	32 1/8   830	35 1/8   910
DEPTH (IN/MM)	28 3/8   725	27 3/8   700	31 1/8   790	36   915	40 3/8   1030	43 3/8   1115
HEIGHT (IN/MM)	44 1/8   1135	48 3/8   1220	48 3/8   1220	52 1/8   1345	56 3/8   1430	57 1/8   1465
HEIGHT TO BOTTOM OF DOOR (IN/MM)	14 3/8   360	14 3/8   370	14 3/8   370	17 3/8   440	18 1/2   470	19 3/8   505
DOOR OPENING DIAMETER (IN/MM)	12 3/8   310	14 3/8   365	14 3/8   365	15 3/8   395	17 3/8   435	17 3/8   435
CYLINDER VOLUME (FT3/L)	3   85	3.7   105	4.6   130	6.4   180	8.8   250	11.7   330
DRAIN OUTLET DIAMETER (IN/MM)	3   75	3   75	3   75	3   75	3   75	3   75
HEIGHT TO CENTERLINE OF DRAIN (IN/MM)	4 3/8   105	4 3/8   105	4 3/8   105	4 3/8   105	4 3/8   105	4 3/8   103
EXTRACTION (G-FORCE)	130G	130G	130G	130G	130G	130G
DYNAMIC LOAD (LB/KN)	330 +/- 640 1.5+/-2.9	420+/-720 1.9+/-3.2	520+/-900 2.4+/-4.0	650+/-1130 2.9+/-5.0	850+/-1420 3.8+/-6.3	1020+/-1650 4.6+/-7.3
DYNAMIC FREQUENCY (HZ)	11.2	10.4	10.4	10.0	9.5	9.0
NOISE LEVEL (DBA)	<70	<70	<70	<70	<70	<70
CRATED WIDTH (IN/MM)	27 3/8   690	29 1/2   750	29 1/2   750	30 1/8   780	33 3/8   860	37   940
CRATED DEPTH (IN/MM)	32 1/8   830	35 3/8   890	37 3/8   950	39 3/8   995	43 1/8   1110	47 3/8   1195
CRATED HEIGHT (IN/MM)	48   1219	53 3/8   1350	53 3/8   1350	56 3/8   1434	61 1/4   1556	62 3/8   1586
CRATED WEIGHT (LB/KG)	276   126	364   166	432   169	522   238	615   280	717   326

**ELECTRICAL REQUIREMENTS (STANDARD)**

STANDARD VOLTAGES (V/Hz/Ø)	120 or 208 - 240   60   1					
POWER (KW) / CKT BREAKER (A) 120V	0.5 / 15	0.6 / 15	0.6 / 15	0.8 / 15	1.2 / 15	1.4 / 15
VOLTAGE/FREQUENCY/PHASE	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1
POWER (KW) / CKT BREAKER (A) 208/240V	0.4 / 15	0.5 / 15	0.5 / 15	0.7 / 15	1.1 / 15	1.3 / 15

**WATER INFORMATION**

INLET FITTINGS (* = 3 INLETS)	3/4 NH   DN20	3/4 NH   DN20	3/4   DN20	3/4*   DN20*	3/4*   DN20*	3/4*   DN20*
FLOW (GPM/LPM @ 44 PSI) (EACH INLET)	5   20	5   20	5   20	8   30	15   60	15   60
RECOMMENDED WATER PRESSURE (PSI/KPA)	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600
MODIFIED ENERGY FACTOR	N/A					
WATER FACTOR (GAL PER CYCLE/DRUM VOLUME)	11.3	11.3	11.3	12.8	12.8	12.8

**WASH FEATURES**

STANDARD WASH PROGRAMS	33	33	33	33	33	33
CUSTOM WASH PROGRAMS	15	15	15	15	15	15
AVAILABLE LANGUAGES	3	3	3	3	3	3
TOP MOUNTED SOAP BOX AND REAR CHEMICAL INJECTION PORTS	•	•	•	•	•	•
NUMBER OF DETERGENT SIGNALS	5	5	5	5	5	5



461 DOUGHTY BOULEVARD, INWOOD, NEW YORK 11096-0338  
 SALES: 516-371-4400 · F 516-371-4204 · sales@laundrylux.com  
 PARTS: 516-371-2000 · F 516-371-4029 · parts@laundrylux.com  
 TECH: 516-371-0700 · F 516-371-4029 · techcare@laundrylux.com